
R45603172 SOCKET SET 1/4" + 3/8" + 1/2"

172 pieces

- > Coupler in acc. with DIN 3120, ISO 1174, with ball locking device
- > Square drive as per DIN 3120, ISO 1174, with ball retention groove
- > 2C reversible ratchet: lever for reversing clockwise/anticlockwise direction, push-button release, fine-toothed, oval head, dual-material handle for ease in handling, for sockets
- > Square plug-in handle 1/4": 1-component handle with female square
- > Socket hex, metric, short, as per DIN 3124, ISO 2725
- > Socket hex, metric, long, as per DIN 3124, ISO 2725
- > Socket, recessed TX
- > Spark plug socket 3/8" with pressed-in holding rubber and extra drive hex Size 21
- > Spark plug socket 1/2" with pressed-in holding rubber
- > Spark plug socket 1/2" with pressed-in holding rubber and extra drive hex Size 24
- > Screwdriver bit socket 1/4", for hex screws: with pressed-in, phosphated pin
- > Screwdriver bit socket 1/4", slotted: with pressed-in, phosphated pin
- > Screwdriver bit socket 1/4" PH: with pressed-in, phosphated pin
- > Screwdriver bit socket 1/4" PZ: with pressed-in, phosphated pin
- > Screwdriver bit socket 1/4" TX: with pressed-in, phosphated pin
- > Screwdriver bit socket 1/4"TX: with drill hole, with pressed-in, phosphated pin
- > Sliding T-bar with slider 1/4": as per DIN 3122, ISO 3315
- > Socket extension 1/4" + 3/8" + 1/2"
- > Universal joint 1/4" + 3/8" + 1/2": screwed-on joint , as per DIN 3123 C 12.5
- > Convertor/slider 3/8" x 1/2": for driving sockets and screwdriver bit sockets
- > Bit adaptor 1/4": with female square and in-hex, for all bits and tools with 1/4" external hex
- > Bit adaptor 3/8": with female square and in-hex, for all bits and tools with 5/16" external hex
- > Bit adaptor 1/2": with female square and in-hex, for all bits and tools with 5/16" external hex

5/16" bits TX with drill hole T40 T45 T50 T55 T60 T70 | 30 mm

- > Bit 1/4", TX: TX BO, TX security, BO, keyway, XZN for holder as per DIN 1173, ISO 6.3
- > Bit 5/16": in-hex, slotted, PH, TX, TX BO for holder as per DIN ISO 1173 D 8
- > Hexagon socket key set: as per DIN ISO 2936
- > For hand-operated screw work
- > Chrome-vanadium steel, matt satin chrome-plated
- > Plastic case in GEDORE red Design
- > Clamp-secured tools
- > Metal hinges/fastener





Code	No.	Contents	Contents continued	L	W	Dp	oieces	∆ kg ∆
3300058	R45603172	1/4" 2C lever reversible ratchet, fine-toothed, 72 teeth 150 mm	3/8" 2C lever reversible ratchet, fine-toothed, 72 teeth 180 mm	452	340	86	172	10.500
		1/4" square plug-in handle 165 mm	3/8" socket hexagon 10 11 12 13 14 15 16 17 18 19					
		1/4" socket hexagon 4 4.5 5 5.5 6 7 8 9 10 11 12 13 14 25 mm	3/8″ socket hexagon 10 11 12 13 14 15 63 mm					
		1/4″ socket hexagon 4 5 6 7 8 9 10 50 mm	3/8" socket TX E10 E11 E12 E14 E16 E18					
		1/4" socket TX E4 E5 E6 E7 E8 25 mm	3/8" spark plug socket 18 mm 65 mm					
		1/4" screwdriver bit socket in-hex 4 4 5 6 37 mm	3/8" socket extension 150 mm					
		1/4" screwdriver bit socket slotted 4 5.5 6.5 7 37 mm	3/8" universal joint 49 mm					
		1/4" screwdriver bit socket cross-head PH 0 1 2 37 mm	Bit adapter 3/8" square x 5/16" hex 30 mm					
		1/4" screwdriver bit socket cross-head PZ 0 1 2 37 mm						
		1/4" screwdriver bit socket TX T8 T9 T10 T15 T20 T25 T27 T30 37 mm	1/2" 2C lever reversible ratchet, fine-toothed, 72 teeth 250 mm					
		1/4" screwdriver bit socket TX with drill hole T8 T9 T10 T15 T20 T25 T27	1/2" socket hexagon 10 11 12 13 14 15 16 17 18 19 20 21					
		T30 37 mm	22 24 27 30 32					
		1/4" socket extension 50 100 mm	1/2″ socket hexagon 16 17 18 19 22 77 mm					
		1/4" sliding T-bar with slider 115 mm	1/2" socket 1/2 TX E20 E24					
		1/4" universal joint 32 mm	1/2" spark plug socket 16 21 mm 65 mm					
		Bit adapter 1/4" sq. x 1/4" hex 25 mm	1/2" socket extension 125 250 mm					
			1/2" universal joint 66 mm					
		1/4" bits TX T5 T6 T7 25 mm	Socket extension piece/slider 3/8" x 1/2" 44 mm					
		1/4" bits TX with drill hole T7 25 mm	Bit adapter 1/2" square x 5/16" hex 38 mm					
		1/4" bits TX plus security T10 T15 T20 T25 T27 T30 T40 T45 25 mm						
		1/4" bits multi-point XZN M5 M6 M8 25 mm	Hexagon socket key 1.5 2 2.5 3 4 5 6 mm					
		1/4" bits keyway M5 M6 M7 M8 M9 25 mm						
		5/16" bits in-hex 7 8 10 12 14 30 mm						
		5/16" bits slotted 8 10 12 30 mm						
		5/16" bits cross-head PH 3 4 30 mm						
		5/16" bits cross-head PZ 3 4 30 mm						
		5/16" bits TX T40 T45 T50 T55 T60 T70 30 mm						